

MATERIAL SAFETY DATA SHEET

May be used to comply with OSHA's Hazard Communication Standard 29 CFR 1910.1200. Standard must be consulted for specific requirements.	HMIS HAZARD RATING		
SAFETEC OF AMERICA	HEALTH	1	0 = INSIGNIFICANT 3 = HIGH
	FLAMMABILITY	1	1 = SLIGHT 4 = EXTREME
	REACTIVITY	0	2 = MODERATE
TRANSPORTATION INFORMATION			
PROPER SHIPPING NAME	Not Regulated		
HAZARD CLASS / PKG. GRP.	None / None		REF. Not Applicable
IDENTIFICATION NUMBER	None		LABEL None Required

SECTION 1 - PRODUCT / COMPANY IDENTIFICATION

IDENTITY (AS USED ON LABEL AND LIST)	Page 1 of 2
Formalin Spill Control (FSC)	
MANUFACTURER'S NAME Safetec of America, Inc.	EMERGENCY TELEPHONE NUMBER (24 Hours) (800) 255-3924
ADDRESS (NUMBER, STREET, P.O. BOX) 887 Kensington Avenue @ William L. Gaiter Pkwy.	TELEPHONE NUMBER FOR INFORMATION (716) 895-1822
(CITY, STATE AND ZIP CODE) Buffalo, NY 14215	DATE PREPARED May 9, 2007 SUPERSEDES September 1, 2004

SECTION 2 - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

HAZARDOUS COMPONENTS (SPECIFIC CHEMICAL IDENTITY; COMMON NAME(S))	CAS #	% (wt.) (OPTIONAL)	OSHA PEL/STEL		ACGIH TLV/TWA/STEL	
			PPM	MG/M ³	PPM	MG/M ³
Carbamidic Compound; CAS proprietary		45 – 65	None Established		None Established	
Superabsorbent polymer; CAS proprietary		45 – 65	5 (PEL)		5 (TLV)	

This product is not known to contain a substance subject to Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR 372 at or above minimal amounts.

SECTION 3 - HEALTH HAZARD DATA

ROUTES OF ENTRY - SIGNS AND SYMPTOMS OF EXPOSURE	EMERGENCY AND FIRST AID PROCEDURES
EYES: May cause slight irritation.	Flush eyes with clear running water for a minimum of 15 minutes while holding eyelids open; if irritation persists, seek medical attention.
SKIN: Prolonged contact with skin may cause slight irritation associated with reddening, itching and inflammation.	Wash thoroughly with soap and water; if irritation persists, seek medical attention.
INGESTION: Ingested in quantity, material may cause gastrointestinal irritation with nausea, vomiting and diarrhea.	Drink large amounts of water. DO NOT induce vomiting. Seek medical attention.
INHALATION: Breathing of dust may cause throat and upper respiratory tract irritation.	Remove to fresh air; seek medical attention if required.

HEALTH HAZARDS (ACUTE AND CHRONIC): Acute effects are possible irritation and discomfort; Chronic exposure to large amounts of this material has not been characterized and the irritating properties of the compound make such an exposure highly unlikely.

CARCINOGENICITY	NTP? No	IARC MONOGRAPHS? No	OSHA REGULATED? No
No additional information			

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Preexisting skin, breathing or kidney disorders may become aggravated through exposure.

MATERIAL SAFETY DATA SHEET

IDENTITY (AS USED ON LABEL AND LIST)

Formalin Spill Control (FSC)

Page 2 of 2

Date: May 9, 2007

SECTION 4 - FIRE FIGHTING MEASURES

FLASH POINT (METHOD USED) Not Applicable	FLAMMABLE LIMITS (% Volume in Air for Lowest Flashing Component) LEL: Not Applicable UEL: Not Applicable
---	--

EXTINGUISHING MEDIA
Water, Dry chemicals, foam, CO₂

SPECIAL FIRE FIGHTING PROCEDURES
Wear NIOSH/MSHA approved self contained breathing apparatus.

UNUSUAL FIRE AND EXPLOSIVE HAZARDS
Spilled material swells and becomes extremely slippery when wet. May form explosive mixtures subject to spontaneous detonation when contaminated with strong acids (nitric or perchloric) or nitrate fertilizers. Use standard safety precautions for finely divided powders. Thermal decomposition may emit toxic and irritating substances.

SECTION 5 - PRECAUTIONS FOR SAFE HANDLING AND USE / LEAK PROCEDURES

STEPS TO BE TAKEN IF MATERIAL IS SPILLED OR RELEASED
In case of accidental spills, provide adequate ventilation; avoid generating dust. Vacuum (using HEPA filter equipped system) if possible to avoid generating airborne dust. Avoid contamination with other materials that may produce an explosion hazard. Place spilled material into a clean, dry container for disposal.

WASTE DISPOSAL METHODS
Dispose of in accordance with Local, State, and Federal regulations. Products classified as non-hazardous may become hazardous waste upon contact with other products. Refer to "40 CFR Protection of Environment Parts 260-299" for complete waste disposal regulations. Consult your Local, State, or Federal Environmental Protection Agency before disposing of any chemicals.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE
Keep container(s) tightly closed when not in use. Store in cool, dry area. Keep this and other chemicals out of reach of children.

SECTION 6 - EXPOSURE CONTROLS / PERSONAL PROTECTION

RESPIRATORY PROTECTION Use NIOSH/MSHA approved or equivalent with high efficiency filter for particulate levels above 0.05mg/m ³	VENTILATION LOCAL EXHAUST: Recommended MECHANICAL (GENERAL): As appropriate
--	---

PROTECTIVE GLOVES Impervious/chemical resistant	EYE PROTECTION Safety goggles
--	----------------------------------

OTHER PROTECTIVE CLOTHING OR EQUIPMENT Ordinarily, none required	WORK / HYGIENIC PRACTICES Practice safe work habits. Use according to label instructions.
---	--

SECTION 7 - PHYSICAL / CHEMICAL PROPERTIES

BOILING POINT Not applicable	BULK DENSITY 49.0 – 53.0 lb./cu. ft.
---------------------------------	---

VAPOR PRESSURE (mm Hg) Not applicable	MELTING POINT 271 – 275°F (partial to full decomposition)
--	--

VAPOR DENSITY (AIR=1) Not applicable	pH Not available
---	---------------------

SOLUBILITY IN WATER Slight	EVAPORATION RATE (n-BUTYL ACETATE=1) Not applicable
-------------------------------	--

APPEARANCE AND ODOR Off-white, granular powder; slight ammoniacal odor	% VOLATILES (BY WEIGHT) Not applicable
---	---

SECTION 8 - STABILITY AND REACTIVITY

STABILITY UNSTABLE: STABLE: XXX	CONDITIONS TO AVOID High humidity, extreme temperatures
---------------------------------------	--

INCOMPATIBILITIES (MATERIALS TO AVOID)
Strong oxidizing agents, strong bases, strong acids

HAZARDOUS DECOMPOSITION OR BYPRODUCTS
Decomposition will not occur if handled / stored properly. Thermal decomposition may emit hydrogen cyanide, ammonia, oxides of nitrogen, carbon monoxide, carbon dioxide.

HAZARDOUS POLYMERIZATION MAY OCCUR: WILL NOT OCCUR: XXX	CONDITIONS TO AVOID None known
---	-----------------------------------

The information contained herein is believed to be accurate but is not warranted to be so. Users are advised to confirm in advance of need that information is current, applicable and suited to the circumstances of use. Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, vendor assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety procedures are followed.