



SPILLTECH

SpillTech
5440 McGinnis Village Place
Suite 102
Alpharetta, GA 30005
Phone: 1-800-228-3877
Fax: 1-800-872-3764
www.spilltech.com

MATERIAL SAFETY DATA SHEET

SECTION I: IDENTIFICATION OF PRODUCT

PRODUCT NAME: NeedlePunch Matting
CHEMICAL FAMILY: Olefin
MANUFACTURER'S NAME: Lenrod Industries

Distribution Location:

SpillTech
Brookley Industrial Complex
1627 O'Donoghue Street
Mobile, AL 36615

Customer Service Telephone Number: 1-800-228-3877

Technical Information Telephone Number: 1-251-694-0102 ext.121

Date Prepared: April 29, 2002

SECTION II: HAZARDOUS INGREDIENTS

<u>INGREDIENTS</u>	<u>PERCENT</u>	<u>CAS NUMBER</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>
Polypropylene	>92%	9003-07-0	N/A	N/A
Minor Additives	<8%	Mixture	N/A	N/A

NOTE:

SpillTech's black needlepunch is a by-product of first-quality needlepunch matting.

SpillTech's gray needlepunch (designated by a "-GR" in the item number) is first quality needlepunch matting.

SECTION III: HAZARDS IDENTIFICATION

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA) RATING:

HEALTH: 0
FLAMMABILITY: 1
REACTIVITY: 0

*Not considered a hazardous material at temperatures below melting point. Not considered a controlled substance or a carcinogen.

SECTION IV: FIRST AID MEASURES

EYE CONTACT: Use eyewash, consult physician if accompanied by pain or irritation.
SKIN CONTACT: N/A
INHALATION: N/A
INGESTION: N/A

SECTION V: FIRE FIGHTING MEASURES

FLASH POINT: >315° C (600° F)
AUTO IGNITION: >550° C (1022° F)
FLAMMABLE LIMITS: N/A
FIRE EXTINGUISHING MEDIA: Water, Foam, CO2, Dry Chemical
SPECIAL FIRE FIGHTING PROCEDURES: Standard procedures for Class A fires
UNUSUAL FIRE AND EXPLOSION HAZARDS: Overheated or molten material may burn slowly with dense smoke. Avoid inhalation of vapors. Sorbents will take on the characteristics/properties of whatever liquid is absorbed. Therefore, all measures must be taken as if you were handling the liquid itself. Sorbents do not make the liquid less hazardous. Always refer to the MSDS for the chemical absorbed before proceeding

SECTION VI: ACCIDENTAL RELEASE MEASURES

Product is fabric made from polyolefin fibers and yarn and the roll may be very heavy. Use caution in the event of spill on uneven ground. Use suitably rated lifting equipment in the event a roll needs to be moved. Dispose of any damaged material in accordance with local, state and federal regulations.

SECTION VII: HANDLING AND STORAGE

Store in dry area. Do not store near open flame, high heat, strong oxidants, or halogenated hydrocarbons. Polyolefin, when heated, becomes very sticky and will burn. Use self-contained air masks to enter smoky area in the event of fire. Adequate ventilation is required to remove decomposition products when temperature exceeds melting point. Avoid contact with melted product. Sorbents will take on the characteristics/properties of whatever liquid is absorbed. Therefore, all measures must be taken as if you were handling the liquid itself. Sorbents do not make the liquid less hazardous. Always refer to the MSDS for the chemical absorbed before proceeding

SECTION VIII: EXPOSURE CONTROLS/ PERSONAL PROTECTION EQUIPMENT

RESPIRATORY PROTECTION: None Required
VENTILATION: None Required
PROTECTIVE GLOVES: None Required
EYE PROTECTION: Safety glasses with side shields are recommended as a good practice for industrial safety.
OTHER PROTECTIVE EQUIPMENT (SPECIFY): None Required

SECTION IX: PHYSICAL DATA

APPEARANCE AND ODOR:	Gray or black & virtually odor free
SPECIFIC GRAVITY:	0.905
BOILING POINT (C):	Not Applicable
MELTING POINT (C):	164° C (328° F)
SOLUBILITY IN WATER:	Insoluble
PERCENT VOLATILE BY VOLUME:	N/A
EVAPORATION RATE:	N/A
VAPOR PRESSURE (mm Hg):	N/A
VAPOR DENSITY (Air = 1):	N/A

SECTION X: TRANSPORT INFORMATION

DOT CLASSIFICATION: Non Hazardous

SECTION XI: WASTE XI DISPOSAL METHOD

Disposal must be done in accordance with local, state and federal regulations based on chemicals adsorbed by products.

Sorbents will take on the characteristics/properties of whatever liquid is absorbed. Therefore, all measures must be taken as if you were handling the liquid itself. Sorbents do not make the liquid less hazardous. Always refer to the MSDS for the chemical absorbed before proceeding

SECTION XII: PREPARATION

This product contains no ingredients subject to reporting under SARA 313 (40 CFR Part 372)

This product may contain ingredients in the fiber lubricant package that are listed under SARA section 311/312: Acute Health Hazard. However, at levels under 1% of the product weight, it is not anticipated that the "Reportable Quantity" threshold will be reached with the typical fabric inventories.

The information contained herein is given in good faith, but no warranty, expressed or implied, is made.

DATE ISSUED: April 29, 2002, February 2005

UPDATED: November 2005

PREPARED BY: SpillTech, Telephone Number: 1-800-228-3877.